


AS08024HB3851B2(00NH)

Air performance



Single wires AWG24, tinned
VCC = red GND = black FG = black
No obstruction within 1mm of air intake

Certifications	CE / UL
U [V DC]	24 [V]
I _{typ} [mA]	1880 [mA]
I _{max} [mA]	2500 [mA]
V _{max} [m³/h]	227,3 [m³/h]
P _{max} [Pa]	862,8 [Pa]
Noise [dB(A)]	72,8 [dB(A)]
Rotation Speed [min ⁻¹]	13500 [min ⁻¹]
Signal / FG [Imp/U]	[Imp/U]
PWM	no
Temp. [°C]	-10 [°C] - 70 [°C]
L10/MTTF @ 40°C [h]	70000 [h] - 350000 [h]
Bearing type	Ball bearing
Weight [kg]	0,219


* Noise and rotation speed are subject to deviations due to tolerance.

ORDER INFORMATION

AS08024HB3851B2(00NH) Art.Nr.: 111112149

Technical changes without notice
26.11.2025

SEPA EUROPE GmbH DE-79427 Eschbach Tel.: +49 7634/59459-0 info@sepa-europe.com



SEPA GmbH

EUROPE

Axial Fan DC



AS08024HB3851B2(00NH)