

UF-T12ABPB0AM1D4A W

Air performance

Single wires AWG22, tinned
VCC = GND = FG =
No obstruction within 1mm of air intake

Certifications	CE / UL
U [V AC]	230 [V]
I _{typ} [mA]	60 [mA]
I _{max} [mA]	120 [mA]
V _{max} [m ³ /h]	180 [m ³ /h]
P _{max} [Pa]	85 [Pa]
Noise [dB(A)]	43 [dB(A)]
Rotation Speed [min ⁻¹]	3200 [min ⁻¹]
Signal / FG [Imp/U]	[Imp/U]
PWM	no
Temp. [°C]	-30 [°C] - 75 [°C]
L10/MTTF @ 40°C [h]	60000 [h] - 240000 [h]
Bearing type	Ball bearing
Weight [kg]	0,29


* Noise and rotation speed are subject to deviations due to tolerance.

ORDER INFORMATION

UF-T12ABPB0AM1D4A W Art.Nr.: 995022099

Technical changes without notice
26.11.2025

SEPA EUROPE GmbH DE-79427 Eschbach Tel.: +49 7634/59459-0 info@sepa-europe.com



SEPA GmbH

EUROPE

Axial Fan AC

UF-T12ABPB0AM1D4A W

Technical changes without notice
26.11.2025

SEPA EUROPE GmbH DE-79427 Eschbach Tel.: +49 7634/59459-0 info@sepa-europe.com